

The EB-L630U fixed lens laser projector offers 6,200 lumens and is ideal for education, corporate, retail and visitor attractions.

As the market leader in 3LCD technology, Epson continues to improve its high brightness laser projectors with even smaller and more compact display solutions. The EB-L630U delivers even more effective, practical and creative display applications across a number of different industries.

Bright, cost-effective display solutions

Providing bolder, brighter, more engaging and impactful displays even in brightlylit environments, the EB-L630U offers impressive 6,200-lumen brightness and WUXGA Full HD resolution at an affordable price. This means that users can upgrade to laser performance and reliability, with reduced power consumption, without paying a premium. It also features: 4K input support, detail enhancement technology, edge blending and wide lens shift to fit challenging installation environments. The EB-L630U is capable of up to 500-inch displays, without any reduction in clarity or vivid detail.

Enhanced connectivity

This display solution offers many different ways to connect, show multiple sources simultaneously and present wirelessly. The EB-L630U comes equipped with futureproofed connectivity options including HDMI and HDBaseT with 4K signal support, 5GHz wireless with enterprise security, upgraded Miracast, built-in media player and support for Epson's ELPWP10 wireless presentation system.

Easy and flexible installation

This stylish and compact projector supports 360 degree installation without compromising the display quality and supports 16:6 ultra-widescreen, HDMI output and edge blending for multi-projector installs.

KEY FEATURES

• 6,200-lumen brightness

Crisp images and bright colours, even in well-lit rooms

- WUXGA resolution Sharp Full HD images for excellent clarity
- Futureproofed connectivity options 4K input support, HDMI, HDBaseT, integrated Wi-Fi and screen mirroring
- Easy, flexible installation Lightweight and compact design with wide lens shift
- Support social distancing Scalable display size of up to 500 inches



EXCEED YOUR VISION

PRODUCT SPECIFICATIONS

TECHNOLOGY		
Projection System	3LCD Technology, RGB liquid crystal shutter	
LCD Panel	0.67 inch with C2 Fine	
IMAGE		
Color Light Output	6,200 Lumen- 4,340 Lumen (economy) In accordance with IDMS15.4	
White Light Output	6,200 Lumen - 4,340 Lumen (economy) In accordance with ISO 21118:2012	
Resolution	WUXGA, 1920 x 1200, 16:10	
High Definition	Full HD	
Aspect Ratio	16:10	
Contrast Ratio	Over 2,500,000 : 1	
Light source	Laser	
Laser Light source	20,000 hours Durability High, 30,000 hours Durability Eco	
Keystone Correction	Manual vertical: ± 30 °, Manual horizontal ± 30 °	
Colour Video Processing	10 Bits	
Colour Reproduction	Upto 1.07 billion colours	
OPTICAL		
Throw Ratio	1.35 - 2.20:1	
Zoom	Manual, Factor: 1 - 1.6	
Projection Lens Zoom Ratio	1.35 - 2.2 : 1	
Lens	Optical	
Lens Shift	Manual - Vertical ± 50 %, horizontal ± 20 %	
Screen Size	50 inches - 500 inches	
Projection Distance Wide	1.4 m - 14.8 m	
Projection Distance Tele	2.4 m - 23.8 m	
Projection Distance Wide/Tele	ə 1.44 m - 23.84 m	
Projection Lens F Number	1.5 - 1.7	
Projection Lens Focal Length	20 mm - 31.8 mm	
Projection Lens Focus	Manual	
CONNECTIVITY		
Interfaces	USB 2.0 Type A, USB 2.0 Type B, RS-232C, Ethernet interface (100 Base-TX / 10 Base-T),	
	Wireless LAN IEEE 802.11a/b/g/n/ac, Wireless LAN b/g/n (2.4GHz), Wireless LAN a/n (5GHz),	
	VGA in (2x), VGA out, HDMI out, HDBaseT, Miracast, Stereo mini jack audio out, Stereo mini	
	jack audio in (2x), HDMI (HDCP 2.3) (2x), USB 2 Type A playback	
Epson iProjection App	Ad-Hoc / Infrastructure	
Network Protocol	HTTPS, IPv6, SNMP, ESC/VP.net, PJLink	
ADVANCED FEATURES		
Security	Kensington lock, Control panel lock, Security cable hole, Wireless LAN unit lock, Wireless LAN	
ocounty	security, Password protection	
2D Colour Modes	Dynamic, Cinema, Presentation, sRGB, DICOM SIM	
Other features	A/V mute, Arc Correction, Auto Power On, Auto source search, Built-in speaker, Customizable	
Other reatures	user logo, Daisy chain Multi-Projection, Digital zoom, Direct Power on/off, Document Camera	
	Compatible, Edge Blending, Home Screen, Horizontal and vertical keystone correction, JPEG	
	Viewer, Long light source life, PC Free, Power on button, Quick Corner, Schedule Function,	
	Screen Mirroring, Split-Screen-Function, Super resolution, Ultra-wide display (16:6), Volume	
Video Oslan Madaa	control, Web Control, Web Remote, Wireless LAN capable, iProjection App	
Video Color Modes	Cinema, Dynamic, Presentation, sRGB, DICOM SIM, Multi Projection	
Projector control	via: Crestron Integrated Partner, Extron IP Link, Extron XTP, AMX Device Discovery, Control4	
	Simple Device Discovery Protocol	

EB-L630U

WHAT'S IN THE BOX

- Power cable
- Remote control incl. batteries
- Cable cover
- User guide
- Warranty Documents
- Main unit





PRODUCT SPECIFICATIONS

EB-L630U

GENERAL		
Power consumption	345 Watt, 258 Watt (economy), 0.3 Watt (standby)	
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz	
Product dimensions	440 x 339 x 136 mm (Width x Depth x Height)	
Product weight	8.4 kg	
Noise Level	Normal: 38 dB (A) - Economy: 27 dB (A)	
Supported Temperature	Temperature Storage -10° C - 60° C	
Supported Humidity	Operation 20% - 80%, Storage 10% - 90%	
	If the projector is suspended from a ceiling or wall mount and installed in an environment with heavy oil smoke or places where oils or chemicals are volatilized, places where a lot of smoke	
	or bubbles are used for event staging, or where aroma oils are frequently burned, it can make	
	certain parts of our products susceptible to a material degradation which over time could	
	break and cause the projector to drop from the ceiling.	
	If you are concerned about the environment in which your projector is installed, or if you have	
	any other questions, please contact our support department and they can provide additional assistance.	
Options	Connection and control box, Document camera, External Speaker, HDBaseT Transmitter,	
	MB22 ceiling mount, Wireless LAN unit	
Loudspeaker	10 Watt	
Room Type / Application	Boardroom, Large Meeting Room / Auditorium, Meeting room / Classroom, Projection	
	Mapping, Signage / Retail, Visitor Attraction	
Positioning	Ceiling Mounted, Desktop	
Colour	White	
OTHER		
Warranty	36 months Carry in	
	Optional warranty extension available	



OPTIONAL ACCESSORIES

- Adapter ELPAP11 Wireless LAN (5GHz) V12H005A01
- Air Filter ELPAF56 L600/EB-14XX Series V13H134A56
- Ceiling Mount (White) ELPMB22
- V12H003B22 • Ceiling Mount (Low profile) - ELPMB30
- V12H526040 • Ceiling Pipe (450mm) - ELPFP13
- V12H003P13
- Ceiling Pipe (700mm) ELPFP14 V12H003P14
- Safety Wire ELPWR01 V12H003W01

LOGISTICS INFORMATION

ѕки	V11HA26040
EAN code	8715946695310
Country of Origin	Philippines



EPSON[®]



* Warranty offers are not available for all countries. Please contact your local Epson representative.

For further information please contact your local Epson office or visit www.epson-europe.com Austria 01 253 49 78 333 Belgium +32 (0)2 792 04 47 Czech 800/142 052 Denmark 44 50 85 85 Finland 0201 552 091 France 09 74 75 04 04

(Cost of local call, operator charges may apply) Germany +49 (0) 2159/92 79 500 Greece +30 211 198 62 12 Hungary 06800 147 83 Ireland 01 436 7742

Italy 02-660321 10 (0,12 /min) Luxembourg +352 27860692 Middle East +9714 8872172 Netherlands +31 (0)20 708 5099 Norway +47 67 11 37 00

Poland 0-0-800 4911299 (0,16 zl/min) Portugal 707 222 111 Russia (095) 777-03-55 Slovakia 0850 111 429 South Africa (+2711) 465-9621

Spain 93 582 15 00 Sweden 0771-400135 (Mobilsamtal - 0,99 kr/min, Lokala samtal - 0,30 kr/min, Utlandssamtal - 0,89 kr/min) Switzerland 022 592 7923 Turkey (0212) 3360303 United Kingdom 0871 222 6702

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice.